

Concrete Rod Hanger

GFC Structa™ 6 High Performance

Allrounder concrete screw -
for heavy loads.

Steel - zinc-plated

The **GFC Structa™ 6** High Performance seismic C1 & C2 rated concrete rod hanger is designed for the easy and safe instalment and suspension of threaded rod for a wide a range of different mechanical, structural and electrical applications. European Technical Assessment certified.

Applications:

- Fire protection
- Air conditioner ducting
- Hanging pipe
- Installing cable trays

Advantages:

- ETA approved
- Fire Rated
- C1 & C2 Seismic rated
- Quick and safe installation – loads can be achieved immediately
- High load capacity
- Suitable for both cracked and non-cracked concrete – option 1 approved
- Easily removable



Item Code	Description (mm)	Drill Diam (mm)	Embedm. Depth (mm)	ETA C1 Cert.	ETA C2 Cert.
S6RH06040	6 x 40 – Structa™6 stud	6	40	✓	
S6RH08060	8 x 60 – Structa™6 stud NEW!	8	60		✓
S6RHC060406	6 x 40 – Structa™6 hanger / M6 Int.	6	40	✓	
S6RHC06040810	6 x 40 – Structa™6 hanger / M8/10 Int.	6	40	✓	
S6RHC0604012	6 x 40 – Structa™6 hanger / M12 Int.	6	40	✓	
S6RHC080601012	8 x 60 – Structa™6 hanger / M10/12 Int. NEW!	8	60		✓

Specifications may be subject to change. We endeavour to ensure data is correct at time of publication.